



ET 型 / ET Core

型号 TYPE	图例 FIG.	尺寸 Dimensions (mm)							G
		A	B	C	D	E	F		
ET20	1	20.1±0.4	20.1±0.4	4.4±0.2	4.0±0.2	16.1±0.3	16.1±0.3	6.1max	
ET20.1/26.3/5.4	1	20.1±0.4	26.3±0.5	5.4±0.2	4±0.2	16.1±0.4	21.6±0.4	2±0.15	
ET20.3/26.3/5.5	1	20.3±0.4	26.3±0.5	5.5±0.3	4±0.2	16.3±0.4	21.6±0.4	2±0.15	
ET23B	1	23.4±0.3	22.0±0.3	3.8±0.2	3.8±0.2	18.9min	17.4min		
ET24	1	24+0.7/-0.4	24+0.7/-0.4	4±0.3	4±0.2	18.9min	18.9min		
ET24D	1	24.0+0.7/-0.4	24.0+0.7/-0.4	4.0±0.3	4.0±0.2	19.2min	19.2min		
ET25E	2	24.5+0.7/-0.3	24.5+0.7/-0.3	7±0.3	6.6±0.2	19.5+0.85/-0.15	19.3min		
ET25B	1	25.5±0.5	25.5±0.5	5.0±0.3	5.0±0.3	19.2min	19.2min		
ET28/34.8/6.4	1	28±0.5	34.8±0.5	6.4±0.3	6.4±0.3	22±0.4	28.8±0.5		
ET28A	1	28.7±0.5	28.7±0.5	5.0±0.3	5.0±0.3	22.2min	22.2min		
ET35B	1	35.3±0.6	35.3±0.6	7.5±0.3	7.5±0.25	27.3±0.5	27.3±0.5	10.2max	

C1	Ae	Le	Amin	Ve	AL(±30%)				重量 g/PCS
					TS5	TS7	TS10	TS13	
2.87	17.60	50.58	17.60	890.30	2400	3200	4300	5600	4.60
2.80	22.36	61.89	21.60	1383.90	2450	3400	4500	5900	7.20
2.73	22.78	62.09	22.00	1414.40	2500	3400	4600	5900	7.30
3.79	15.09	57.17	14.44	862.80	1800	2500	3300	4200	4.50
3.46	17.64	61.11	16.00	1077.90	2000	2700	3600	4700	5.60
3.64	16.98	61.88	16.00	1050.80	1900	2500	3400	4400	5.50
1.62	37.23	60.12	34.30	2238.40	4300	5800	7700	10000	11.60
2.29	27.35	62.60	25.00	1712.00	3100	4200	5500	7200	8.60
2.10	39.29	82.71	38.40	3249.60	3200	4400	5900	7700	16.90
2.57	27.87	71.61	25.00	1995.60	2700	3700	4900	6300	10.40
1.50	58.59	86.69	56.25	5079.30	4800	6500	8600	11000	26.40